

Rotule SA

PM17-00-502-DURBAL - PM17-00-502-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/sa/pm17-00-502-durbal>

PM17-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating		
type	approx. weight [kg]	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	Y	Y ₀	C	C ₀
PM 17 -00	-502	17	M 20 x 1,5	21,0	48	25	22	16				
type		l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'		
PM 17		62,5	36	105	3,5	2,5	7,0	0,401			2,35	2,46
											875	5575
											2680	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507675
Diam. intérieur	17 mm
Diam. extérieur	48 mm
Epaisseur	22 mm
Type	SA
Poids	401 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE