

Rotule SA BRM06-60-502-DURBAL - BRM06-60-502-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/sa/brm06-60-502-durbal>

BRM06-60-502



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished, rolled thread

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3402 D10k (sizes 6 to 10) DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]				
type	type	d ₁	d ₂			
BRM 06 -60	-502	6	M 6			
		d ₄	d ₅			
		9,0	20			
		l ₁	l ₂			
		9	6,75			
		h	36			
measurements [mm]		weight	calculation factors	rotational speed limit	basic load rating	
type	l ₁	l ₂	α [°]	Y	Y ₀	
BRM 06	22	12	8,0	0,019	2,09	2,19
					1350	1900
					450	450

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952509099
Diam. intérieur	6 mm
Diam. extérieur	20 mm
Epaisseur	9 mm
Type	SA
Poids	19 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE