

Rotule SI
BRF10-60-502-DURBAL - BRF10-60-502-DURBAL
<https://www.123roulement.ch/roulement-palier/rotule/si/brf10-60-502-durbal>

BRF10-60-502



rod end housing:
stainless steel 1.4534, hardened, bearing
race superfinished

inner ring:
stainless steel, hardened,
surface superfinished


lubrication:
aluminium-complex soap-grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing in stainless steel**



female thread;
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K



order number		measurements [mm]										
type	right-hand thread	left-hand thread	d1	d2	d3	d4	d5	d6	d7	b1	b2	h
BRF 10 -60	-502		10	15,0	M 10	12,0	28	19	14	10,5	43	
measurements [mm]			weight			calculation-factors		rotational speed limit		basic load rating		
type	l	l1	l2	SW	α [°]	[kg]	Y	Y0	C [Nmm]	Cdyn [N]	Cstat [N]	rating [N]
BRF 10	20	6,5	15	17	8,0	0,072	1,90	1,81	1225	3100	1000	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952509259
Diam. intérieur	10 mm
Diam. extérieur	28 mm
Epaisseur	14 mm
Type	SI
Poids	72 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ch
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE