

Rotule SA BRM1-2-00-502-DURBAL - BRM1-2-00-502-DURBAL

<https://www.123roulement.ch/roulement-palier/rotule/sa/brm1-2-00-502-durbal>

BRM1/2-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
dimensions in inches

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DN 3425 D11A (sizes 1/4 and 3/8)
DN 71 412 H1 (sizes 1/2 and 1/1)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [inches]							
type	right hand thread, left hand thread	d ₁	d ₂ class 2	d ₃	d ₄	d ₅	b ₁	b ₂	
BRM 1/2 -00	-502	500	5000-20 UNF	574	1.311	624	.472		
measurements [inches]		weight		calculation factors		rotational speed limit		basic load rating	
type	h	l	l ₃	α [°]	Y	Y ₂	n _{max} [min ⁻¹]	C [N]	C ₀ [N]
BRM 1/2	2.460	1.496	.846	7,5	0,109	1,74	1,82	1125	4850 1850

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952510293
Diam. intérieur	12.7 mm
Diam. extérieur	33.3 mm
Epaisseur	15.85 mm
Type	SA
Poids	109 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE