

Douille à aiguilles FC-4-K-NADELLA - FC-4-K-NADELLA

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/fc-4-k-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F _z mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min*	Suitable needle bush
4	FC-4-K	4	8	6	0.349	28000	HK0408

Shaft Ø mm	Gapping			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Mounting		Max. mm	Min. mm	
4	7.984	3.980	4.004	11	Max. mm 4.000	Min. mm 3.985	Max. mm 7.983	Min. mm 7.984	0.001

CARACTÉRISTIQUES PRODUIT

Marque	NADELLA
N° Ean13	3616060472502
Diam. intérieur	4 mm
Diam. extérieur	8 mm
Épaisseur	6 mm
Poids	1 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE