

Roulement autre AXNA522-NADELLA - AXNA522-NADELLA

<https://www.123roulement.ch/roulement-palier/roulement-autre/axna522-nadella>

Precision combined bearings,
with adjustable axial preload



AXNA and AXNAT series



- 1) 6% of dynamic axial load
- 2) with axial load equal to preload
- 3) rigidity of a single thrust bearing with load equal to preload
- 4) hexagon socket shallow head cap screw DIN 91

Shaft Ø mm	Designation		d mm	D mm	F _d mm	D _m mm	B mm	C mm	B ₁ mm	r mm	Mounting				
	AXNA	AXNAT									Screw TCEI ⁴⁾ class 12.9	N° screws	E mm	Torque Nm	
5	S 22		5	22	7.3	17	12.5	12	4	4	0.35				

Load Ratings kN				Speed Ratings min ⁻¹	Preload ¹⁾ N	Rotation ²⁾ torque Nmm	Rigidity K ³⁾ N/mm	Shaft threading	Weight kg	Designation
radial	axial		Stat. Co							
Dyn. C	Stat. Co	Dyn. C	Stat. Co	19 000	252	55	32	5 x 0.8	0.021	AXNA S 22
2.35	2.65	4.0	9.4							

CARACTÉRISTIQUES PRODUIT

Marque	NADELLA
N° Ean13	3663952530055
Diam. intérieur	5 mm
Diam. extérieur	17 mm
Épaisseur	12 mm
Poids	21 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE