

Roulement autre

ARNBT35110-NADELLA - ARNBT35110-NADELLA

<https://www.123roulement.ch/roulement-palier/roulement-autre/arnbt35110-nadella>

Precision combined bearings,
with adjustable axial preload



AXNBT and ARNBT
series



- 1) 6% of dynamic axial load
- 2) with axial load equal to preload
- 3) rigidity of a single thrust bearing with load equal to preload
- 4) hexagon socket shallow head cap screw DIN 91

| Shaft Ø mm | Designation | | | d | D | D _A | Dm | B | C | B ₂ | r | r ₁ | Screw | Mounting | Torque | | | | |
|------------------|-------------|----------|----------|--------|----|----------------|----|----|------|----------------|----|----------------|--------|----------|--------|----|----|----|----|
| | AXNBT | ARNBT | ARNBT | mm | mm | mm | mm | mm | mm | mm | mm | mm | TCE II | N° | E | s | Nm | | |
| 35 | | series 1 | series 2 | 35 110 | 35 | 110 | 45 | 73 | 57.7 | 66 | 20 | 23 | 1.30 | 0.85 | 6x25 | 12 | 88 | 11 | 24 |

| Load Ratings kN | | | | Speed rating min ⁻¹ | Preload ¹⁾ N | Rotation ²⁾ torque Nmm | Rigidity K to N/mm | Weight kg | Designation |
|-----------------|----------|--------|----------|-----------------------------------|----------------------------|---|-----------------------|--------------|--------------|
| radial | | axial | | | | | | | |
| Dyn. C | Stat. Co | Dyn. C | Stat. Co | | | | | | |
| 34.5 | 67.0 | 86.0 | 228.0 | 4 300 | 5 250 | 2 900 | 1 520 | 2.029 | ARNBT 35 110 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | NADELLA |
| N° Ean13 | 3663952530826 |
| Diam. intérieur | 35 mm |
| Diam. extérieur | 73 mm |
| Épaisseur | 66 mm |
| Poids | 2029 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE