

Rotule SA
MPL-07-F-DUNLOP - MPL-07-F-DUNLOP
<https://www.123roulement.ch/roulement-palier/rotule/sa/mpl-07-f-dunlop>

MALE ROD ENDS

DUNLOP

MP-SERIES: MP - MPS - MP SS

Description
MP-Series is our 3-piece standard range of self-lubricating general purpose male rod ends suitable for light to medium heavy industrial/mechanical load applications requiring low friction and good wear resistance, available in both metric and imperial bore and thread sizes. They have excellent moisture resistance and require no maintenance and have a wide operating temperature range.

Material Specifications
Housing: Steel 230M07PB and forged 80M44, zinc plated and clear trivalent plastic and stainless steel 303L & 304 forged. Race: GR-Nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated and stainless steel 440C and 316L/316. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303L.

Features
Metric & imperial thread & bore sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
Studded option

Possible Applications
Light to medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
Precision equipment
No maintenance
Linear movement

Temperature Range
-30°C to +170°C

Specification
ELV & RoHS compliant

Housing: Steel 230M07PB (Stress 0.2 - 0.2)
Forged 80M44 (Stress 0.8 - 1.6)
Zinc Plated and Clear Trivalent Passivate

Race: GR-Nylon LV-3H

Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MPL-07F		7/16	7/16 BSP	0.542	0.437	1.125	2.125	1.375	0.586	19,750

Interchange table

Dunlop	Rose	Tuthill	Alinabal	SKF	Asahi	IKO
MP-M (metric)	MMMP	MJ-M	MPM-M	SAKH-M	JAM EC	POS-EC
MP (imperial)	BMMP	MJ	PM-	-	-	POSB-EC

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.

For stainless steel add 'SS' to part no. For example 'MP-M03 SS'

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3663952556130
Diam. intérieur	11.113 mm
Diam. extérieur	28.575 mm
Epaisseur	11.1 mm
Type	SA
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.ch
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE