

Roulement à bille simple rangée 1640-DC-NICE - 1640-DC-NICE

<https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/1640-dc-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|----------------------------|-----------------------------|---|------------------------|------------------------------------|------------------------------------|---------------------------------------|---------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| | | | | | | +0.000 +0.000 -0.0005 -0.013 | +0.000 +0.000 -0.0005 -0.013 |
| 1640™ | DC | | | | | 0.9750 22.225 | 2.0000 50.800 |
| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | | |
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC C ₀ (lb) (N) | W ⁰ (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) | |
| 0.5625 14.288 | 2967 13203 | 1350 6008 | 0.29 0.13 | 1.113 28.27 | 1.780 44.70 | 0.035 0.89 | |

ⓘ Weights given are for greased and sealed versions
Ⓜ 1638 and larger +0.000/-0.006 (+0.000/-0.15)

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|--------------|
| Marque | NICE |
| N° Ean13 | 637400291839 |
| Diam. intérieur | 22.225 mm |
| Diam. extérieur | 50.8 mm |
| Épaisseur | 14.288 mm |
| Poids | 130 g |
| Conditionnement | - |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE