

Roulement à bille simple rangée 1641-SS-NICE - 1641-SS-NICE

<https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/1641-ss-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|---------|-------------|-------------|---------------|---------------|------|---------------------------------------|---------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| | | | | | | +0.000 +0.000 -0.0005 -0.013 | +0.000 +0.000 -0.0005 -0.013 |
| 1641™ | | | | SS | | 1.9000 25.400 | 2.0000 50.800 |

| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|------------------------------|--|------------------------|------------------------------------|------------------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lbs) (N) | STATIC C ₀ (lbs) (N) | W ⁰ (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) |
| 0.5625 14.288 | 2967 13203 | 1350 6008 | 0.26 0.12 | 1.197 30.40 | 1.780 44.70 | 0.035 0.89 |

Weights given are for greased and sealed versions

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | NICE |
| N° Ean13 | 3663952557830 |
| Diam. intérieur | 25.4 mm |
| Diam. extérieur | 50.8 mm |
| Épaisseur | 14.288 mm |
| Poids | 120 g |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE