


Roulement à bille simple rangée 3002-NS-NICE - 3002-NS-NICE

<https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/3002-ns-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3002™					NS	0.2500 +0.005 -0.13 -0.000 -0.00	0.5675 +0.000 -0.013 -0.005 0

WIDTH		BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
B (in) (mm)	C (lbs) (N)	Co (lbs) (N)	W (lb) (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)	
0.2500 0.350	255 1135	170 757	0.02 0.01	0.330 8.38	0.614 15.60	0.012 0.30	

Width for sealed versions = 0.3125 (7.938) Weights given are for greased and sealed versions
3038 and larger +.0000/-0.005 (-.000/-0.13)

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558042
Diam. intérieur	6.35 mm
Diam. intérieur	1/4" inch
Diam. extérieur	17.463 mm
Diam. extérieur	11/16" inch
Epaisseur	6.35 mm
Epaisseur	1/4" inch
Poids	10 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE