

Roulement à bille simple rangée 3005-NS-NICE - 3005-NS-NICE

<https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/3005-ns-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm) +0.005 +0.13 -0.000	O.D. D (in) (mm) +0.000 +0.00 -0.013
3005™					NS	0.3125 7.938	0.9063 23.020

WIDTH B (in) (mm) +0.005 +0.00 -0.005 -0.13	BASIC LOAD RATINGS		WEIGHT W (lb) (kg) 0.04 0.02	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lbs) (N) 300 1355	STATIC Co (lbs) (N) 300 1355		da min (in) (mm) 0.503 12.76	Da max (in) (mm) 0.778 19.76	r max (in) (mm) 0.012 0.30
0.3125 7.938	300 1355	300 1355	0.04 0.02	0.503 12.76	0.778 19.76	0.012 0.30

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3005 and larger +0.000/-0.005 (+0.00/-0.13)

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558196
Diam. intérieur	7.938 mm
Diam. intérieur	5/16" inch
Diam. extérieur	23.02 mm
Diam. extérieur	29/32" inch
Epaisseur	7.938 mm
Epaisseur	5/16" inch
Poids	20 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE