

Roulement à bille simple rangée 3007-DC-NICE - 3007-DC-NICE

<https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/3007-dc-nice>

3000 Series® Semi-Ground Radial Bearings NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3007™	DC					+0.005 +0.13 -0.000 -0.00	+0.000 +.50 -0.005 -0.013
						0.4375 11.113	0.9063 23.020

WIDTH B (in) (mm)	BASIC LOAD RATINGS		WEIGHT W (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)		da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.3125 7.938	300 1508	300 1355	0.03 0.01	0.517 13.13	0.778 19.76	0.015 0.38

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3038 and larger +.0000/-0.005 (-.000/-0.13)

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558257
Diam. intérieur	11.113 mm
Diam. intérieur	7/16" inch
Diam. extérieur	23.02 mm
Diam. extérieur	29/32" inch
Epaisseur	7.938 mm
Epaisseur	5/16" inch
Poids	10 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE