

Roulement à bille simple rangée 3020-SC-NICE - 3020-SC-NICE

<https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/3020-sc-nice>

3000 Series® Semi-Ground Radial Bearings (con't) NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3020™		SC				+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 -0.013
						0.4375 11.113	1.3750 34.925

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)	W ^⓪ (lb) (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)
0.4375 11.113	940 4183	860 3783	0.12 0.05	0.658 16.71	1.203 30.58	0.025 0.64

^⓪ Weights given are for greased and sealed versions
^⓪ 3028 and larger +.0005/-0.005 (+.000/-0.13)

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558462
Diam. intérieur	11.113 mm
Diam. extérieur	34.925 mm
Épaisseur	11.113 mm
Poids	50 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE