

Roulement à bille simple rangée 3040-NS-NICE - 3040-NS-NICE

<https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/3040-ns-nice>

3000 Series® Semi-Ground Radial Bearings (con't) NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3040™					NS	+0.005 +0.13 -0.000 -0.005	+0.000 +0.00 -0.0005

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)	W ^⓪ (lb) (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)
0.5625 14.288	1480 6598	1350 6008	0.29 0.13	1.113 28.27	1.760 44.70	0.035 0.89

^⓪ Weights given are for greased and sealed versions
^⓪ 3038 and larger +0.0005/-0.0005 (+0.001/-0.013)

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558899
Diam. intérieur	22.225 mm
Diam. intérieur	7/8" inch
Diam. extérieur	50.8 mm
Diam. extérieur	2" inch
Epaisseur	14.288 mm
Epaisseur	9/16" inch
Poids	130 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE