

# Rotule TSM MS-M12-10-C-DUNLOP - MS-M12-10-C-DUNLOP

<https://www.123roulement.ch/roulement-palier/rotule/tsm/ms-m12-10-c-dunlop>

MALE ROD ENDS 



**MS SERIES: MS - MSS - MS SS**

**Description:**  
MS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

**Material Specifications:**  
Housing: Steel 230M4779p (Sae) MS - M12 Forged 800M44 (Sae) M14 - M20 Zinc Plated and Clear Trivalent Passivate  
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate  
Ball: Bearing Steel 100C-6, Case Hardened and Electroless Nickel Plated

**Features:**  
Metric & Imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Studed and stainless steel options.

**Possible Applications:**  
Medium heavy industrial mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

**Temperature Range:**  
-20°C to +250°C

**Specification:**  
ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MS-M12-10C		10	M12x1.25	16	12.00	32	54	33	15.40	23,600

**Interchange table**

Dunlop	Rose	Aurora	Askubal	SKF	ASAHI	IKO	Fluro
MS-M (metric)	MNC	MM-M-T and MB-M-T	KA-P	SAKB-P	JAM-EC	POS-EC	GASW
MS (imperial)	RMC	MM-T and MB-T	-	-	-	POSB-EC	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

For stainless steel add 'SS' to part no. For example 'MS-M05 SS'

## CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3663952559193
Diam. intérieur	10 mm
Diam. extérieur	32 mm
Epaisseur	16 mm
Type	TSM
Filetage	Filetage à droite
Lubrification	sans
Charge statique	0.0236 kN
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE