

Roulement à bille simple rangée 7508-DL-NICE - 7508-DL-NICE

https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/7508-dl-nice

7500 Series™ Heavy Duty Precision Ground Radial Bearings NICE

- PRECISION GRINDING ON ALL CONTACT SURFACES - GRINDING TO THE 100 MICROMETER FINISH
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 5000 RPM
- THROUGH HARDENED BEARING STEEL
- REFINED FINISH
- WIDER RETAINER STANDARDS
- DOUBLE SEALED VERSIONS
- EXCELLENT OPERATING TEMPERATURE CONTACT BALLS WITH THERMALLY STABLE
- AVAILABLE WHILE SEALED OR OPEN
- ALL BEARINGS MEET A RULP AND ISO9001 CERTIFIED MANUFACTURING TO ORDER
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHOCK AND VIBRATION

BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7508™	+0.000 -0.005 -0.013	+0.000 -0.005 -0.018	+0.000 +0.00 -0.05	0.0625 1.58	7500 19.05	1.009 25.63

PRINCIPLE DIMENSIONS			BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
G (in) (mm)	H (in) (mm)	J (in) (mm)	R (in) (mm) Radius	Dynamic C _d (lb) (N)	Static C _s (lb) (N)	W ⊕ (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.136 3.45	0.042 1.07	1.9219 48.82	0.035 0.89	8595 11548	1085 4581	0.33 0.15	0.750 19.05	1.500 38.10	0.036 0.89

⊕ When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
⊕ Tolerance for 7514™ and larger is +0.000/-0.006 (+.000/-0.15)
⊕ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
⊕ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of FSC Nippon Bearings.

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3616060473271
Diam. intérieur	12.7 mm
Diam. extérieur	44.45 mm
Epaisseur	15.88 mm
Poids	150 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE