


Roulement à bille simple rangée 5561-V-NICE - 5561-V-NICE

<https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/5561-v-nice>

5000 Series® Single Row. Unground Flanged Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA							
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)		D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5561™	V	0.250 +0.005/-0.000 +13/-000	0.687 +0.005/-0.000 +19/-000	0.250 +0.010/-0.010 +25/-25	0.250 0.35	0.250 1.27	0.750 19.05	0.250 1.27	0.250 +0.010/-0.010 +25/-25

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY						
		REVOLUTIONS PER MINUTE						
NO.	SIZE	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)	
10	1/8	0.02	110	77	53	43	30	21
		3.18	490	343	238	191	134	93

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560212
Diam. intérieur	6.35 mm
Diam. extérieur	17.45 mm
2nd Diam. extérieur	19.05 mm
Epaisseur	6.35 mm
Poids	10 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE