


## Roulement à bille simple rangée 5881-V-NICE - 5881-V-NICE

<https://www.123roulement.ch/roulement-palier/roulement-bille/simple-rangee/5881-v-nice>

**5000 Series® Single Row Unground Flanged Radial Bearings** **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE		O.D.		WIDTH		G
		A (in) (mm)	B (in) (mm)	C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	
5881™	V	+0.005/-0.000 +13/-00	+0.005/-0.000 +13/-00	+0.010/-0.010 +25/-25	0.463 0.062	1.800 38.10	0.125 3.18	+0.010/-0.010 +25/-25

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY						
		REVOLUTIONS PER MINUTE						
		50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)	
NO.	SIZE							
18	3/16 4.75	0.12 0.08	375 1669	281 1181	160 803	145 648	101 449	71 318

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

### CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560267
Diam. intérieur	12.7 mm
Diam. intérieur	1/2" inch
Diam. extérieur	34.93 mm
Diam. extérieur	1 3/8" inch
2nd Diam. extérieur	38.1 mm
2nd Diam. extérieur	1 1/2" inch
Epaisseur	11.76 mm
Epaisseur	0.463" inch
2nd Epaisseur	13.87 mm
2nd Epaisseur	0.546" inch
Poids	50 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE