

Accessoire de palier 7611-DL-NICE - 7611-DL-NICE

<https://www.123roulement.ch/roulement-palier/paliers/accessoires/7611-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring NICE®

- PRECISION ENGINEERED FOR ALL CONTACT SURFACES SUBJECT TO THE "BEC" STANDARD
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOAD
- MAX SPEED RANGE: 5000-8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STANDARD
- SHOULD BE KEPT SEPARATE
- EXCELLENT APPROPRIATE ANGLE OF CONTACT
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHARP FILLET RADIUS. THIS WILL ENHANCE LIFE IN OPTION
- INDICATED FOR APPLICATIONS WHERE EXCESSIVE HEAT AND VIBRATION ARE REQUIRED.

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
	+0.0008 +0.002 -0.0000 -0.001	+0.0000 +0.005 -0.0008 -0.001	+0.000 +0.00 -0.005 -0.13			+0.005 +0.13 -0.005 -0.13
7611™	.8675 17.45	1.7900 45.45	0.8250 15.88	0.0825 1.50	1.000 25.40	0.138 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (lb) (N)	Static C _s (lb) (N)	W (lb) (kg)
0.042 1.07	1.922 49.82	1.982 50.35	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2196 11548	1025 4581	0.30 0.14

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ③ Tolerance for 7613™ and larger is +0.0005-0.0006 (+0.0001-0.015) ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC NICE® Bearings.

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3616060473424
Diam. intérieur	17.46 mm
Diam. extérieur	25.63 mm
Épaisseur	15.88 mm
Poids	140 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE