

Rotule TSM

MXL-05-4-DUNLOP - MXL-05-4-DUNLOP

<https://www.123roulement.ch/roulement-palier/rotule/tsm/mxl-05-4-dunlop>

MALE ROD ENDS

MALE ROD ENDS

DESCRIPTION:
MX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: B17M 40, heat treated to 80/90 tons/in² tensile, Phosphated all over.
Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged B17M40, Heat Treated to 80/90 tons/in² tensile and Phosphated all over.

Balls: Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	M	X	Static Load Rating (Newtons) Radial
MXL-05-4		.7500	.375	.320	.375	.812	1.625	1.062	3/16 UNF	22	11770

Interchange table

Dunlop	Rose	NMB
MXL-Metric	RRL-M	RRL-M
MX-Imperial	RRL-I	RRL-I

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.
'0' in part number denotes grease nipple is fitted.

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060550859
Diam. intérieur	6.35 mm
Diam. intérieur	1/4" inch
Diam. extérieur	20.624 mm
Diam. extérieur	0.812" inch
Epaisseur	9.525 mm
Epaisseur	3/8" inch
Type	TSM
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1
Norme	Sans norme

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE