

Rotule SI
FSL-M22-DUNLOP - FSL-M22-DUNLOP
<https://www.123roulement.ch/roulement-palier/rotule/si/fsl-m22-dunlop>

FEMALE ROD ENDS



F5 SERIES: F5 - F5S - F5 SS

Description:
F5 Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 230M07Pb and forged 680M4s, zinc plated and clear trivalent passivate and stainless steel 302L and forged 20A. Inner Ring: Steel 670M40 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 100Cr6, heat treated, polished & electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, extended wear life, no maintenance, stainless steel options.

Possible Applications:
Medium/heavy industrial mechanical applications, construction equipment, agricultural equipment, motor sport and recreational vehicles requiring high precision motion control.

Temperature Ranges:
-200°C to +250°C

Specification:
ELV & RoHS compliant

Housing: Steel 230M07Pb (500a M05 - M12)
Forged 680M4s (500a M14 - M22)
Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 670M40, Zinc Plated and Clear Trivalent Passivate

Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liner: High strength PTFE composite

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating (Newtons) Radial
FSL-M22		22	M22X1.50	28	20.00	54	84	37	25.80	32	52,750

Interchange table

Dunlop	Rose	Aurora	Askubal	SKF	Asahi	IKO	Fluro
FS-M (metric)	MFC	MW-M-T and MG-M-T	KI-P	SKB-F	JAF-EC	PHS-EC	QISW
FS (imperial)	RFC	MW-T and MG-T	-	-	PHSB-EC	-	-

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060554352
Diam. intérieur	22 mm
Diam. extérieur	28 mm
Epaisseur	20 mm
Type	SI
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ch
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE