

Rotule SI

FX-M12-G-DUNLOP - FX-M12-G-DUNLOP

<https://www.123roulement.ch/roulement-palier/rotule/si/fx-m12-g-dunlop>

FEMALE ROD ENDS

DESCRIPTION:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

MATERIAL SPECIFICATIONS:
Housing: 817M 40, heat treated to 80/90 tons/m² tensile. Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

FEATURES:
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

POSSIBLE APPLICATIONS:
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

TEMPERATURE RANGE:
-40°C to +150°C

SPECIFICATION:
ELV & RoHS compliant

Housing: Forged 817M40, Heat Treated to 80/90 tons/m² tensile and Phosphate all over. Ball: Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newtons) Radial
FX-M12G		T2	19.0	16.2	19.0	41.2	54.2	28.0	20.3	M12 x 1.75	22	49000

Interchange table

Dunlop	Rose	NMB
FX-M (metric)	RBJ-M	RBJ-M
FX (imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060555069
Diam. intérieur	12 mm
Diam. intérieur	0.472" inch
Diam. extérieur	19 mm
Diam. extérieur	0.748" inch
Epaisseur	16.02 mm
Epaisseur	0.631" inch
Type	SI
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE