

Rotule GE

GE100-FW-DUNLOP - GE100-FW-DUNLOP

https://www.123roulement.ch/roulement-palier/rotule/ge/ge100-fw-dunlop

SPHERICAL BEARINGS



Outer Ring: Bearing Steel 100Cr6, Case Hardened

GE FW SERIES

Description:
GE-FW-Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the balls and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction, they do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated. Liner: PTFE fabric. Seals: Polyurethane.

Features:
Metric size
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications:
Medium heavy industrial mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control.

Temperature Range:
-52°C to +121°C

Specification:
ELV & RoHS compliant

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE100FW		100	85	95	160	3,075,000

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060557391
Diam. intérieur	100 mm
Diam. extérieur	160 mm
Épaisseur	85 mm
Type	GE
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE