

Douille à aiguilles BAM4420-IKO - BAM4420-IKO

<https://www.123roulement.ch/roulement-palier/roulement-aiguilles/douille/bam4420-iko>



BAM BHAM
 $t_1 (F_w \geq 22.225)$
 $t_2 (F_w \leq 20.638)$

| Boundary dimensions mm(inch) | | | | Standard mounting dimensions mm | | | | Basic dynamic load rating | Basic static load rating | Adjusted dynamic load rating | Adjusted static load rating |
|------------------------------|----------------|----------------|-----|---------------------------------|------|--------------------|------|---------------------------|--------------------------|------------------------------|-----------------------------|
| F _w | D | C | B | HUB dia. | | Mounting bore dia. | | C | CF | CF | CF |
| | | | | Max. | Min. | Max. | Min. | Min. | Min. | Min. | Min. |
| 68.800 (2.709) | 79.375 (3.125) | 31.751 (1.250) | 2.4 | | | | | 54600 | 139000 | 30000 | 68000 |

CARACTÉRISTIQUES PRODUIT

| | |
|------------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060601070 |
| Diam. intérieur | 69.85 mm |
| Diam. extérieur | 79.375 mm |
| Epaisseur | 31.75 mm |
| Vitesse limite | 3500 rpm |
| Charge dynamique | 54.6 kN |
| Charge statique | 139 kN |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE