


## Rondelle ondulée fendue

### SWSW-107.95-95-0.76-5-SS - SWSW-107.95-95-0.76-5-SS

<https://www.123roulement.ch/accessoire/rondelle/rondelle-ondulee-fendue/swsw-107.95-95-0.76-5-ss>

Do = Outside diameter (max) (mm)  
Di = Inside diameter (min) (mm)  
t = Thickness (mm)  
H = Free height approx.  
H1 = Load at height  
L1 = Load at L1 (±15% Newton)  
DB = Bearing's outside diameter  
Dh = Free fit in hole diameter  
Dr = Free fit over hole diameter  
N = Number of waves



Split Wave Spring Washers

| Part Number    | Di (mm) | t (mm) | L1 (N)  | H1 (mm) | Do (mm) | N | H (mm) |
|----------------|---------|--------|---------|---------|---------|---|--------|
| WWG04250210695 | 95,00   | 0,76   | 306,927 | 2,769   | 107,95  | 5 | 5,33   |

## CARACTÉRISTIQUES PRODUIT

|                          |           |
|--------------------------|-----------|
| Marque                   | GEN       |
| Diam. intérieur          | 95 mm     |
| Epaisseur                | 0.76 mm   |
| Matière                  | INOX      |
| Conditionnement          | 1         |
| Charge à L1              | 306.927 N |
| Charge en hauteur        | 2.769     |
| Diamètre extérieur (max) | 107.95 mm |
| Nombre d'ondes           | 5         |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE