


Rondelle ondulée fendue

SWSW-279.40-258.32-0.81-9-SS - SWSW-279.40-258.32-0.81-9-SS

<https://www.123roulement.ch/accessoire/rondelle/rondelle-ondulee-fendue/sws-279.40-258.32-0.81-9-ss>

Do = Outside diameter (max) (mm)
Di = Inside diameter (min) (mm)
t = Thickness (mm)
H = Free height approx.
H1 = Load at height
L1 = Load at L1 (+/-15 % Newton)
DB = Bearing's outside diameter
Dh = Free fit in hole diameter
D = Free fit over hole diameter
N = Number of waves



Split Wave Spring Washers

| Part Number | Di (mm) | t (mm) | L1 (N) | H1 (mm) | Do (mm) | N | H (mm) |
|----------------|---------|--------|---------|---------|---------|---|--------|
| WWG1100035066B | 258,32 | 0,81 | 738,405 | 3,962 | 279,40 | 9 | 6,89 |

CARACTÉRISTIQUES PRODUIT

| | |
|--------------------------|-----------|
| Marque | GEN |
| Diam. intérieur | 258.32 mm |
| Epaisseur | 0.81 mm |
| Matière | INOX |
| Conditionnement | 1 |
| Charge à L1 | 738.405 N |
| Charge en hauteur | 3.962 |
| Diamètre extérieur (max) | 279.4 mm |
| Nombre d'ondes | 9 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE