


## Rondelle ondulée fendue

**SWSW-115.01-101.38-0.76-5-SS - SWSW-115.01-101.38-0.76-5-SS**

<https://www.123roulement.ch/accessoire/rondelle/rondelle-ondulee-fendue/sws-115.01-101.38-0.76-5-ss>

Do = Outside diameter (max) (mm)  
Di = Inside diameter (min) (mm)  
t = Thickness (mm)  
H = Free height approx.  
H1 = Load at height  
L1 = Load at L1 (+/-15 % Newton)  
DB = Boreing's outside diameter  
Df = Free fit in hole diameter  
De = Free fit over hole diameter  
N = Number of waves



Split Wave Spring Washers

Part Number	Di (mm)	t (mm)	L1 (N)	H1 (mm)	Do (mm)	N	H (mm)
WWMG06353159S	101.38	0.76	315.899	6.35	115.01	5	3.18

## CARACTÉRISTIQUES PRODUIT

Marque	GEN
Diam. intérieur	101.38 mm
Epaisseur	0.76 mm
Matière	INOX
Conditionnement	1
Charge à L1	315.899 N
Charge en hauteur	6.35
Diamètre extérieur (max)	115.01 mm
Nombre d'ondes	5

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE