


Roulement conique 302-22-R-JTEKT - 302-22-R-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/302-22-r-jtekt>

Single-row tapered roller bearings
metric series



Koyo

Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾	
d	D	T	B	C	C _r	C _{0r}	Grease lub.		Oil lub.
22	50	15.25	14	12	29.3	30.9	8 100	11 000	302/22R

Dimension series to ISO 355 (DIN 625)	Load center (mm)	Mounting dimensions (mm)						Constant e	Axial load factors		Reference Mass (kg)			
		d ₁ min.	d ₁ max.	D ₁ max.	D ₂ min.	S _a min.	S _b min.		r _a max.	r _b max.		Y ₁	Y ₀	
—	12.2	27.5	30	44.5	41	46	2	3	1	1	0.37	1.60	0.88	0.144

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400426
Diam. intérieur	22 mm
Diam. extérieur	50 mm
Épaisseur	15.25 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE