


## Roulement conique 303-22-XR-JTEKT - 303-22-XR-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/303-22-xr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
22	56	17.25	16	13	36.3	36.6	7 700	10 000	303/22XR					
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.		r <sub>1</sub> max.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
—	15.7	30.5	31	47.5	44	52	3	4	1.5	1.5	0.59	1.02	0.56	0.210

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400440
Diam. intérieur	22 mm
Diam. extérieur	56 mm
Épaisseur	17.25 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE