


## Roulement conique 30315-DR-JTEKT - 30315-DR-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/30315-dr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
75	160	40	37	26	222	266	2 100	2 900	30315DR					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>1</sub> max.	r <sub>2</sub> max.	Constant e	Axial load factors Y <sub>1</sub>	Axial load factors Y <sub>0</sub>	(Refer. 1) Mass (kg)	
—	48.8	89	91	148	127	151	6	14	2.5	2	0.81	0.74	0.41	3.48

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250122149
Diam. intérieur	75 mm
Diam. extérieur	160 mm
Épaisseur	40 mm
Poids	3516 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE