

## Roulement conique 30320-JR-JTEKT - 30320-JR-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/30320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
100	215	51.5	47	39	4	3	422	521	1 800	2 400	30320JR			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>α</sub> min.	d <sub>α</sub> max.	D <sub>α</sub> min.	D <sub>α</sub> max.	S <sub>α</sub> min.	S <sub>α</sub> max.	r <sub>α</sub> min.	r <sub>α</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2GB	42.7	118	127	201	184	200	6	12.5	3	2.5	0.35	1.74	0.96	8.49

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952410593
Diam. intérieur	100 mm
Diam. extérieur	215 mm
Epaisseur	51.5 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE