

Roulement conique 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/32320-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ |
|--------------------------|-----|------|----|----|-------------------------|-----------------|-----------------|------------------|--------------------------------------|----------|---------------------------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | |
| 100 | 215 | 77.5 | 73 | 60 | 579 | 783 | 1 800 | 2 400 | | | 32320JR |

| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) |
|--|--------------------|--------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|------------|--------------------|----------------|----------------------|
| | | d _{1a} min. | d _{1a} max. | d _{2a} min. | d _{2a} max. | S _{1a} min. | S _{1a} max. | S _{2a} min. | S _{2a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | |
| 260 | 53.9 | 118 | 123 | 201 | 177 | 200 | 8 | 17.5 | 3 | 2.5 | 0.35 | 1.74 | 0.96 | 13.0 | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952410623 |
| Diam. intérieur | 100 mm |
| Diam. extérieur | 215 mm |
| Épaisseur | 77.5 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE