

## Roulement conique 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/32320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm) |     |      |    |    | Basic load ratings (kN) |                 |                 |                  | Limiting speeds (min <sup>-1</sup> ) |          | Bearing No. <sup>1)</sup> |
|--------------------------|-----|------|----|----|-------------------------|-----------------|-----------------|------------------|--------------------------------------|----------|---------------------------|
| d                        | D   | T    | B  | C  | C <sub>r</sub>          | C <sub>0r</sub> | C <sub>90</sub> | C <sub>100</sub> | Grease lub.                          | Oil lub. |                           |
| 100                      | 215 | 77.5 | 73 | 60 | 579                     | 783             | 1 800           | 2 400            |                                      |          | 32320JR                   |

  

| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                     |                     |                     |                     |                     |                     |                     |                     |                     | Constant e | Axial load factors |                | (Refer. 1) Mass (kg) |
|--|--------------------|--------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|------------|--------------------|----------------|----------------------|
|  |                    | d <sub>1</sub> min.      | d <sub>1</sub> max. | D <sub>1</sub> min. | D <sub>1</sub> max. | S <sub>1</sub> min. | S <sub>1</sub> max. | r <sub>1</sub> min. | r <sub>1</sub> max. | r <sub>2</sub> min. | r <sub>2</sub> max. |            | Y <sub>1</sub>     | Y <sub>0</sub> |                      |
| 260                                    | 53.9               | 118                      | 123                 | 201                 | 177                 | 200                 | 8                   | 17.5                | 3                   | 2.5                 | 0.35                | 1.74       | 0.96               | 13.0           |                      |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952410623 |
| Diam. intérieur | 100 mm        |
| Diam. extérieur | 215 mm        |
| Épaisseur       | 77.5 mm       |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE