

Roulement conique 30322-D-JTEKT - 30322-D-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/30322-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
110	240	54.5	50	36	385	429	1 400	1 900	30322D					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d ₁ min.	d ₂ max.	D ₁ max.	D ₂ min.	S _α min.	S _β min.	r _α max.	r _β max.	Constant e	Axial load factors Y ₁	Axial load factors Y ₀	(Refer. 1) Mass (kg)	
—	71.5	128	135	226	205	222	6	18	3	2.5	0.81	0.74	0.41	10.2

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250122460
Diam. intérieur	110 mm
Diam. extérieur	240 mm
Épaisseur	54.5 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE