


Roulement conique 30324-D-JTEKT - 30324-D-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/30324-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
120	260	59.5	55	38	4	3	430	512	1 200	1 700	30324D

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d ₁ min.	d ₁ max.	D ₁ min.	D ₁ max.	S ₁ min.	S ₁ max.	r ₁ min.	r ₁ max.		Y ₁	Y ₀		
—	77.8	138	145	246	219	239	6	21	3	2.5	0.81	0.74	0.41	13.0

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250122507
Diam. intérieur	120 mm
Diam. intérieur	4.724" inch
Diam. extérieur	260 mm
Diam. extérieur	10.236" inch
Epaisseur	59.5 mm
Epaisseur	2.343" inch
Poids	13000 g
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE