


## Roulement conique 32964-JR-JTEKT - 32964-JR-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/32964-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                     |                     | Basic load ratings (kN) |                     |                     |                     | Limiting speeds (min <sup>-1</sup> ) |            | Bearing No. <sup>1)</sup> |                |                      |      |
|--|--------------------|--------------------------|---------------------|---------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                   | C                   | C <sub>r</sub>          | C <sub>0r</sub>     | C <sub>90</sub>     | C <sub>100</sub>    | Grease lub.                          | Oil lub.   |                           |                |                      |      |
| 320                                    | 440                | 76                       | 76                  | 57                  | 1 060                   | 2 270               | 640                 | 850                 |                                      |            | 32964JR                   |                |                      |      |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                     |                     |                         |                     |                     |                     |                                      | Constant e | Axial load factors        |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>1</sub> min.      | d <sub>2</sub> max. | D <sub>1</sub> max. | D <sub>2</sub> min.     | S <sub>1</sub> min. | S <sub>2</sub> min. | r <sub>1</sub> max. | r <sub>2</sub> max.                  |            | Y <sub>1</sub>            | Y <sub>0</sub> |                      |      |
| 3FD                                    | 85.0               | 338                      | 342                 | 426                 | 401                     | 426                 | 12                  | 19                  | 3                                    | 2.5        | 0.42                      | 1.44           | 0.79                 | 34.0 |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952412085 |
| Diam. intérieur | 320 mm        |
| Diam. extérieur | 440 mm        |
| Epaisseur       | 76 mm         |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE