


## Roulement conique 32330-R-JTEKT - 32330-R-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/32330-r-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	r	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.	
150	320	114	108	90	5	1240	1790	1200	1600	32330R

Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	78.4	172	187	302	263	298	10	17	4	3	0.35	1.74	0.96	42.0

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250233319
Diam. intérieur	150 mm
Diam. intérieur	5.906" inch
Diam. extérieur	320 mm
Diam. extérieur	12.598" inch
Epaisseur	114 mm
Epaisseur	4.488" inch
Poids	42000 g
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE