

## Roulement conique 32938-JR-JTEKT - 32938-JR-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/32938-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
190	260	45	45	34	2.5	2	366	789	1 200	1 600	32938JR			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>1</sub> min.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
4DC	55.0	202	204	250	235	252	8	11	2	2	0.48	1.26	0.69	6.89

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250125751
Diam. intérieur	190 mm
Diam. extérieur	260 mm
Epaisseur	45 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE