

## Roulement conique 32238-JR-JTEKT - 32238-JR-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/32238-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.					
190	340	97	92	75	5	4	1 090	1 740	1 000	1 300	32238JR				
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1</sub> min.	d <sub>1</sub> max.	D <sub>1</sub> min.	D <sub>1</sub> max.	S <sub>α</sub> min.	S <sub>α</sub> max.	S <sub>β</sub> min.	S <sub>β</sub> max.	r <sub>α</sub> min.	r <sub>α</sub> max.		r <sub>β</sub> min.	r <sub>β</sub> max.	
4GD	81.9	212	216	322	286	323	12	22	4	3	0.44	1.38	0.76	36.6	

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952421537
Diam. intérieur	190 mm
Diam. extérieur	340 mm
Epaisseur	97 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE