

Roulement conique 32048-JR-JTEKT - 32048-JR-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/32048-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ |
|--------------------------|-----|----|----|----|-------------------------|-----------------|-----------------|------------------|--------------------------------------|----------|---------------------------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | |
| 240 | 360 | 76 | 76 | 57 | 924 | 1720 | 870 | 1200 | | | 32048JR |

| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
|----------------------------------------|--------------------|--------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|------------|--------------------|----------------|----------------------|------|
| | | d ₁ min. | d ₂ max. | D ₁ max. | D ₂ min. | S ₁ min. | S ₂ min. | r ₁ max. | r ₂ max. | | Y ₁ | Y ₀ | | |
| 4FD | 78.5 | 258 | 261 | 346 | 318 | 346 | 12 | 19 | 3 | 2.5 | 0.46 | 1.31 | 0.72 | 26.8 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 4549250123795 |
| Diam. intérieur | 240 mm |
| Diam. extérieur | 360 mm |
| Épaisseur | 76 mm |
| Conditionnement | - |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE