


Roulement conique 19150R-19281-JTEKT - 19150R-19281-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/19150r-19281-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
38.100	71.438	15.875	16.520	11.908	1.6	1.0	46.1	53.8	5 700	7 600

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.		<i>Y</i> ₁	<i>Y</i> ₂		Inner ring
19150R	19281	14.5	45.0	43.0	63.0	66.0	1.6	1.0	0.44	1.35	0.74	0.167	0.105

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952426570
Diam. intérieur	38.1 mm
Diam. intérieur	1 1/2" inch
Diam. extérieur	71.438 mm
Diam. extérieur	2 13/16" inch
Epaisseur	15.875 mm
Epaisseur	5/8" inch
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE