


Roulement conique 27881-27820-JTEKT - 27881-27820-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/27881-27820-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
38.100	80.035	24.608	23.698	18.512	3.6	1.6	73.2	91.6	5 200	6 900

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
27881	27820	22.2	53.0	47.0	68.0	75.0	3.6	1.6	0.56	1.07	0.59	0.378	0.208

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952426648
Diam. intérieur	38.1 mm
Diam. extérieur	80.035 mm
Épaisseur	24.608 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE