


## Roulement conique 4395-4335-JTEKT - 4395-4335-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/4395-4335-jtekt>

Single-row tapered roller bearings  
inch series Koyo



| Boundary dimensions (mm) |          |          |          |          |                          |                                       | Basic load ratings (kN) |                        | Limiting speeds (min <sup>-1</sup> ) |          |
|--------------------------|----------|----------|----------|----------|--------------------------|---------------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i>                 | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> <sub>max.</sub> | <i>r</i> <sub>1</sub> <sub>min.</sub> | <i>C</i> <sub>r</sub>   | <i>C</i> <sub>10</sub> | Grease lub.                          | Oil lub. |
| 42.070                   | 90.488   | 39.688   | 40.386   | 33.338   | 3.6                      | 3.2                                   | 132                     | 169                    | 4 500                                | 6 000    |

| Bearing No. |            | Load center (mm) | Mounting dimensions (mm) |                       |                       |                       |                                       |                                       | Constant | Axial load factors    |                       | (Refer.) Mass (kg) |            |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|---------------------------------------|---------------------------------------|----------|-----------------------|-----------------------|--------------------|------------|
| Inner ring  | Outer ring | <i>a</i>         | <i>d</i> <sub>a</sub>    | <i>d</i> <sub>b</sub> | <i>D</i> <sub>a</sub> | <i>D</i> <sub>b</sub> | <i>r</i> <sub>a</sub> <sub>max.</sub> | <i>r</i> <sub>b</sub> <sub>max.</sub> | <i>e</i> | <i>Y</i> <sub>1</sub> | <i>Y</i> <sub>2</sub> | Inner ring         | Outer ring |
| 4395        | 4335       | 25.6             | 58.0                     | 51.0                  | 77.0                  | 85.0                  | 3.6                                   | 3.2                                   | 0.28     | 2.11                  | 1.16                  | 0.751              | 0.459      |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952426969 |
| Diam. intérieur | 42.07 mm      |
| Diam. extérieur | 90.488 mm     |
| Épaisseur       | 39.688 mm     |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE