

## Roulement conique 25582-25520-JTEKT - 25582-25520-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/25582-25520-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



| Boundary dimensions (mm) |          |          |          |          |                          | Basic load ratings (kN)       |                       | Limiting speeds (min <sup>-1</sup> ) |             |          |
|--------------------------|----------|----------|----------|----------|--------------------------|-------------------------------|-----------------------|--------------------------------------|-------------|----------|
| <i>d</i>                 | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> <sub>max.</sub> | <i>r</i> <sub>1</sub><br>min. | <i>C</i> <sub>r</sub> | <i>C</i> <sub>10</sub>               | Grease lub. | Oil lub. |
| 44.450                   | 82.931   | 23.812   | 25.400   | 19.050   | 5.2                      | 0.8                           | 77.2                  | 100                                  | 4 800       | 6 300    |

  

| Bearing No. |            | Load center (mm) | Mounting dimensions (mm) |                       |                       |                       |                               |                               | Constant | Axial load factors    |                       | (Refer.) Mass (kg) |            |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|-------------------------------|-------------------------------|----------|-----------------------|-----------------------|--------------------|------------|
| Inner ring  | Outer ring | <i>a</i>         | <i>d</i> <sub>a</sub>    | <i>d</i> <sub>b</sub> | <i>D</i> <sub>a</sub> | <i>D</i> <sub>b</sub> | <i>r</i> <sub>a</sub><br>max. | <i>r</i> <sub>b</sub><br>max. | <i>e</i> | <i>Y</i> <sub>1</sub> | <i>Y</i> <sub>2</sub> | Inner ring         | Outer ring |
| 25582       | 25520      | 17.5             | 59.0                     | 51.0                  | 74.0                  | 77.0                  | 5.2                           | 0.8                           | 0.33     | 1.79                  | 0.99                  | 0.361              | 0.200      |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952427041 |
| Diam. intérieur | 44.45 mm      |
| Diam. intérieur | 1 3/4" inch   |
| Diam. extérieur | 82.931 mm     |
| Diam. extérieur | 3.265" inch   |
| Epaisseur       | 23.812 mm     |
| Epaisseur       | 15/16" inch   |
| Conditionnement | 1             |

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE