


Roulement conique 2984-2924-JTEKT - 2984-2924-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/2984-2924-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
46.038	85.000	25.400	25.608	20.638	3.6	1.2	80.0	106	4 600	6 100

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
2984	2924	18.9	58.0	52.0	76.0	80.0	3.6	1.2	0.35	1.73	0.95	0.389	0.220

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952427331
Diam. intérieur	46.038 mm
Diam. extérieur	85 mm
Épaisseur	25.4 mm
Conditionnement	1

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE