


Roulement conique 375-374-JTEKT - 375-374-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/375-374-jtekt>

Single-row tapered roller bearings
inch series Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|----------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> ₁ min. | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 50.800 | 93.264 | 20.638 | 22.225 | 15.083 | 2.4 | 1.2 | 84.4 | 98.5 | 4 200 | 5 600 |

| Bearing No. | | Load center (mm) <i>a</i> | Mounting dimensions (mm) | | | | | | Constant <i>e</i> | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------------------|--------------------------|-----------------------|-----------------------|-----------------------|----------------------------|----------------------------|----------------------|-----------------------|-----------------------|-----------------------|------------|
| Inner ring | Outer ring | | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 375 | 374 | 17.1 | 60.0 | 57.0 | 85.0 | 88.0 | 2.4 | 1.2 | 0.34 | 1.77 | 0.97 | 0.416 | 0.174 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952427690 |
| Diam. intérieur | 50.8 mm |
| Diam. extérieur | 93.264 mm |
| Épaisseur | 20.638 mm |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE