

Roulement conique 389-382A-JTEKT - 389-382A-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/389-382a-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|----------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> ₁ min. | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 55.575 | 96.838 | 21.000 | 21.946 | 15.875 | 2.4 | 0.8 | 80.4 | 101 | 3 900 | 5 200 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|----------------------------|----------------------------|----------|-----------------------|-----------------------|--------------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 389 | 382A | 17.4 | 65.0 | 61.0 | 89.0 | 92.0 | 2.4 | 0.8 | 0.35 | 1.69 | 0.93 | 0.452 | 0.177 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952428130 |
| Diam. intérieur | 55.575 mm |
| Diam. intérieur | 2.188" inch |
| Diam. extérieur | 96.838 mm |
| Diam. extérieur | 3 13/16" inch |
| Epaisseur | 21 mm |
| Epaisseur | 0.827" inch |
| Conditionnement | 1 |

contact@123roulement.ch

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE