


## Roulement conique 65237-65500-JTEKT - 65237-65500-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/65237-65500-jtekt>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> <sub>max.</sub>	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
60.325	127.000	44.450	44.450	34.925	3.6	3.2	208	269	3 300	4 400

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)
Inner ring	Outer ring		<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> <sub>max.</sub>	<i>r</i> <sub>b</sub> <sub>max.</sub>		<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	
65237	65500	35.2	82.0	71.0	107.0	119.0	3.6	3.2	0.49	1.23	0.68	1.59 1.02

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428406
Diam. intérieur	60.325 mm
Diam. extérieur	127 mm
Épaisseur	44.45 mm
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE