


## Roulement conique 6389-6320-JTEKT - 6389-6320-JTEKT

<https://www.123roulement.ch/roulement-palier/roulement-rouleaux/conique/6389-6320-jtekt>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
66.675	135.755	53.975	58.007	44.450	6.4	3.2	266	357	3 000	4 000

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.		<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>		Inner ring
6389	6320	34.8	91.0	77.5	117.0	126.0	6.4	3.2	0.32	1.85	1.02	2.15	1.37

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428673
Diam. intérieur	66.675 mm
Diam. intérieur	2 5/8" inch
Diam. extérieur	135.755 mm
Diam. extérieur	5.345" inch
Epaisseur	53.975 mm
Epaisseur	2 1/8" inch
Conditionnement	1

[contact@123roulement.ch](mailto:contact@123roulement.ch)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE